













AVANT Traffic Barriers



TECHNICAL DATA

| VERSION | MOTORS | LENGTH (max.) | HEIGHT (max.) | OPENING TIME (sec.) | OPERATING TEMPERATURE | MAINTENANCE | BRC SUITABLE |
|---|--|---|---|--|--|---|---|
|   RESIDENTIAL INDUSTRIAL |  1 |  10 |  5 ÷ 12 |  -20° +65° |  EASY |  NO |  |

OPTIONAL





AVANT Traffic Barriers



Vertical Gates - Vertikaltor - Portail à élévation verticale - Cancelli ad Alzata Verticale



1 Traffic Barrier HY Series

PROFESSIONAL USE



2 Traffic Barrier EM STD Series

RESIDENTIAL USE



3 Traffic Barrier EM PRO Series

PROFESSIONAL USE



1 TRAFFIC BARRIER HY SERIES SPECIFICATIONS:


| | |
|--|---|
| Electric Motor - Elektromotor Moteur électrique - Motore elettrico | 1,1 KW - 230 V |
| Motorization - Motorisierung Motorisation - Motorizzazione | Hydraulic with high pressure power unit |
| Using Frequency - Betrieb Fréquence d'utilisation - Frequenza di utilizzo | 80% highly intensive |
| Working Temperature - Betriebstemperatur Temp. de fonctionnement - Temp. di funzionamento | From -30°C to +60°C |
| Protection Degree - Schutzart Degré de protection - Grado di protezione | IP55 |
| Length - Länge Longueur - Lunghezza | 2,50 - 10,00 m |
| Opening time - Öffnungszeit Temps d'ouverture - Tempo di apertura | ~ 12 sec. |

2 TRAFFIC BARRIER EM STD SERIES SPECIFICATIONS:


| | |
|--|---------------------------------------|
| Electric Motor - Elektromotor Moteur électrique - Motore elettrico | 1-phase 230 Vac $\pm 10\%$, 50-60 Hz |
| Motorization - Motorisierung Motorisation - Motorizzazione | Electromechanical |
| Using Frequency - Betrieb Fréquence d'utilisation - Frequenza di utilizzo | 1.000 op./day |
| Working Temperature - Betriebstemperatur Temp. de fonctionnement - Temp. di funzionamento | From -20°C to +60°C |
| Protection Degree - Schutzart Degré de protection - Grado di protezione | IP54 |
| Length - Länge Longueur - Lunghezza | 3,00 - 6,00 m |
| Opening time - Öffnungszeit Temps d'ouverture - Tempo di apertura | ~ 5 sec. |

3 TRAFFIC BARRIER EM PRO SERIES SPECIFICATIONS:

| | |
|--|---------------------------------------|
| Electric Motor - Elektromotor Moteur électrique - Motore elettrico | 1-phase 230 Vac $\pm 10\%$, 50-60 Hz |
| Motorization - Motorisierung Motorisation - Motorizzazione | Electromechanical |
| Using Frequency - Betrieb Fréquence d'utilisation - Frequenza di utilizzo | 10.000 op./day |
| Working Temperature - Betriebstemperatur Temp. de fonctionnement - Temp. di funzionamento | From -30°C to +60°C |
| Protection Degree - Schutzart Degré de protection - Grado di protezione | IP54 |
| Length - Länge Longueur - Lunghezza | 3,00 - 8,00 m |
| Opening time - Öffnungszeit Temps d'ouverture - Tempo di apertura | ~ 7 sec. |



DIMENSIONS



DIMENSIONS

